

## Pinoten Ethernet Switch PG0204P72w

Unmanaged PoE Switch with 4x10/100/1000Base-T PoE + 2x10/100/1000Base-T



4x10/100/1000Base-T PoE + 2x10/100/1000Base-T Ethernet Switch, provides a seamless connection network, the PoE power port can auto detect and power the powered devices that comply with IEEE802.3af, IEEE802.3at, IEEE802.3bt standards. Port 1 supports IEEE802.3af/at/bt, max. PoE++ 60w, Port 2-4 support IEEE802.3af/at max 30W/port.

### Feature

- Comply with IEEE 802.3, IEEE 802.3u, IEEE802.3af/at/bt standards
- Ethernet port supports 10/100/1000M adaptive and PoE functions
- Flow control mode: full-duplex adopts IEEE 802.3x standard, half-duplex adopts back pressure standard
- Support Port Auto-flip (Auto MDI/MDIX)
- Automatically supplied to adaptive devices
- Panel indicator monitoring status and help failure analysis
- Support PoE Watchdog Function
- Fanless Cooling with 0 dB Noise Level
- Designed for 24/7 Operation
- Lightning Protection Surge: General Mode 6KV, Differential Mode 4KV, ESD 8KV.

### Specifications

Fixed port	6*10/100/1000 Base-T
PoE	Port 1 supports 802.3af, 802.3at, 802.3bt; Port 2-4 support 802.3af, 802.3at
Mainboard power	≤3W
Total Power consumption	≤72W
Switching Capacity	12Gbps
Throughput	8.9Mpps
MAC Address table	4K
Buffer	2M Bytes
Forwarding delay	<10us
MDX/MIDX	Support
Jumbo Frame	10KBytes
Input Voltage	AC 100-240V 50/60Hz
Operating Temperature	-10°C~+50°C
Relative Humidity	5%~90% (non-condensing)
Thermal methods	Fan-less, natural cooling
Product Size (L*W*H)	202*140*44mm
Weight	0.7KG
MTBF	100,000 hours